

klemko®



Model: **860114**

Input voltage range	180~230VAC 47~63Hz
Output Voltage	12V±0.5V
Output current	0 ~ 8.3A
Output power	Rated power: 100W
Efficiency	> 80%
Size	255(L)X69(W)X55(H)mm 1600gr
Output mode	Constant voltage output
Cooling	Convection cooling
Operation ambient temperature	-30 ~ +40°C
Working humidity	0 ~ 95% relative humidity
Storage temperature	-40 ~ +70°C
Input output Withstand Voltage	3750VAC/1min Drain Current <5mA
Functions	Over current protection , Short circuit protection
Waterproof rate	IP67
Safety standards	IEC61347 & IEC60598
EMC standards	EN55015 & EN61000 & EN61547

klemko[®]



Model: **860114**

Input voltage range	180~230VAC 47~63Hz
Output Voltage	12V±0.5V
Output current	0 ~ 8.3A
Output power	Rated power: 100W
Efficiency	> 80%
Size	255(L)X69(W)X55(H)mm 1600gr
Output mode	Constant voltage output
Cooling	Convection cooling
Operation ambient temperature	-30 ~ +40°C
Working humidity	0 ~ 95% relative humidity
Storage temperature	-40 ~ +70°C
Input output Withstand Voltage	3750VAC/1min Drain Current <5mA
Functions	Over current protection , Short circuit protection
Waterproof rate	IP67
Safety standards	IEC61347 & IEC60598
EMC standards	EN55015 & EN61000 & EN61547