

The **Airtech Mould Control Pack** contains Radolite Sterilising Solution concentrate for removing black mould and two pots of Mould Eradication Additive for stirring into emulsion paint or wallpaper paste to prevent its return. The wash and additive are easy and safe to use and will provide effective protection against mould growth.



Form Supplied	Twin pack, liquid concentrates
Pack Contents	500ml Radolite, 2 x 50g Mould Eradication Additive 1 pair protective gloves, 1 pair protective goggles 1 paint brush and 1 sponge.
Colour Range	Clear
HSE No	4593
Contains	7.5% w/w Benzalkonium Chloride.
Properties	The pack provides enough materials to treat up to 40m² of walls and ceilings, adequate for most mould growth outbreaks. For larger or very severe outbreaks Fungi-Chek ready mixed paints are also available. Airtech also supplies other Condensation control products including Positive Input Ventilation systems, and Extract fans. For further details of these products contact our office at the address below or contact your local agent.
Usage/Preparation	Use of the pack is a simple two stage process: 1. Dilute the Radolite in the ratio of 500 ml concentrate to 4.5 litres of water. Wash affected areas with Radolite sterilising wash to remove and kill existing mould. Two applications may be necessary in severe cases. 2. Add the Mould Eradication Additive to the chosen emulsion paint, wallpaper paste or cement based tile grout and stir in thoroughly using a mechanical mixer. Use as normal. The pack provides enough materials to treat up to 40 m² of walls and ceilings.
General	There are basic measures to assist in the control of condensation and black mould. These methods are particularly helpful in the domestic environment but can be applied equally to commercial, catering, leisure or medical establishments. It is always important to reduce the risk of condensation by observing the following simple recommendations. • Ensure rooms are always warm and properly ventilated, maintaining some low heating throughout the day if possible. • When cooking, washing, bathing or drying clothes, keep the door closed and the window open - this prevents warm moist air moving to colder areas of the building. • In cold weather keep some heating on all the time. • If a paraffin or flueless gas heater is used ensure a window is open a little (every litre of paraffin produces about 1 litre of water). • Improve internal/external wall insulation. • Use ventilation where appropriate, such as the Airtech PIV units and/or Extract fans.