

Ducting length – 150x70mm



Ducting Dimension:	150x70mm
Warranty:	3yr
Material:	100% Recycled Rigid PVC
Free Area:	9,450mm ²
Operating Temperatures:	-15°C to +60°C
Ducting Colour:	Grey

Rigid PVC ventilation ducting delivers a durable, efficient, and cost-effective solution for modern airflow systems. Available in a wide range of lengths to suit any installation, this robust ducting ensures smooth air movement with minimal resistance, improving overall system performance. Its lightweight yet sturdy construction makes it easy to handle on-site, while the corrosion-resistant PVC material guarantees long-term reliability in both residential and commercial environments. Making ventilation sustainable is our main aim through continuously improving our processes to reduce waste throughout our products lifecycle and significantly increasing the use of recycled plastic from the circular economy in the manufacturing of our products.

Type	Detail		Cat. No.	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)
Flat Channel Length	300mm Length		58030	151	71	300	0.351
	400mm Length		58040	151	71	400	0.468
	1000mm Length		58100	151	71	1000	1.17
	1500mm Length		58150	151	71	1500	1.755
Bends/ Connectors	Horizontal 90° Bend		58500	-	-	-	-
	Vertical 90° Bend		58600	-	-	-	-
	Elboq 90° Bend to 125mm		58400	-	-	-	-
	Connector		58200	-	-	-	-
Support	Clip		58220	-	-	-	-

KEY: Connector = Female Male

DISCOVER MORE!
Click on the buttons

Terminations

Ancillaries



Kits

Fire
Solutions

Available ducting sizes

(a) Storage of Ducting Products: All straight duct lengths are supplied either wrapped or within boxes, surrounded with white protective packaging to help mitigate damaging effects of sunlight exposure. Do not remove the white reflective packaging and leave in sunlight. UV exposure breaks down the polymer chains, resulting in a weaker molecular bond within the PVC, leading to reduced tensile strength and flexibility. On receipt of goods, we recommend all PVC ducting products are immediately stored in a cool, shaded place to avoid damage due to heat build-up within the packaging. Any extrusions (lengths of product) should be stored horizontally and supported along the whole length of the product. In summer months, heat can build up inside packaging faster and there is a chance that PVC goods could become warped if stored incorrectly. Manrose will not be liable for any damage caused to ducting or PVC products through incorrect storage. This part comes in Grey. Whilst we will look to maintain the colour of Grey, by the nature of adopting a recycled plastic the colour and shade may vary at any given time.

MANROSE®

